

# Material Safety Data Sheet

Emergency Phone: (316) 945-9328 24-Hour CHEMTREC (800) 424-9300 CHEMTREC, D.C. Area 800-483-7616

## I. Chemical Product And Company Data

**PRODUCT:** PROFILE CONDITIONER - PC33  
**CHEMICAL FAMILY:** SOLVENT  
**REVISION DATE:** MARCH 2005  
**MANUFACTURER:** Balco, Inc.  
 2626 S. Sheridan, Wichita, KS 67217

Health	1
Flammability	3
Reactivity	1
Personal Protection	H

## II. Composition / Information On Ingredients

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). Where a proprietary ingredient is shown, the identity may be made available as provided in this standard. All components of this product are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

HAZARDOUS INGREDIENTS	CAS NO	EXPOSURE LIMITS			CONTENT
		TLV	STEL	PEL	
Ethyl Acetate	141-78-6	400ppm	N/A	400ppm	97%
Organic Acid	Trade Secret	None	None	None	3%

### California Proposition 65 ingredients

None

### Section 313 Supplier Notification

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 (40 CFR 372)

None

## III. Hazards Identification

HMIS Hazard Rating No. 1

PRIMARY ROUTE OF ENTRY: Eye and skin contact, breathing and ingestion.

Symptoms of Exposure

**Skin Contact:** Frequent or prolonged contact may irritate and cause dermatitis, or aggravate an existing condition.

**Eyes:** Product may cause severe irritation, redness, tearing and blurred vision.

**Inhalation:** Vapors/mist can be irritating to nose and mucous membranes. High exposures may result in dizziness, headaches, anesthesia, drowsiness, unconsciousness and other central nervous system effects.

**Ingestion:** Not expected to be a relevant route of exposure, although it may cause permanent damage to the mouth, throat and stomach.

**IV. First Aid Measures**

Inhalation Remove victim from exposure. If difficulty with breathing, administer oxygen and seek medical assistance

Eyes Flush eyes with cold water for a minimum of 15 minutes, lifting lower and upper eye lids throughout. Seek immediate medical attention.

Skin Immediately remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.

Ingestion Do not induce vomiting, get immediate medical attention, if vomiting occurs spontaneously keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious person.

**V. Fire Fighting Methods**

HMIS Hazard Rating No. 3  
Flash Point: 26 °F  
General Hazard: Decomposition and combustion products may be toxic.  
Auto-Ignition Temp.: 800 °F  
Limits of Flammability LEL: 2.2% UEL: 11%  
Extinguishing Media: For small fires, use water spray, foam, CO<sub>2</sub> or dry chemical. For large fires, use water spray or fog.  
Special Fire & Unusual Hazards: Move containers from area if it can be done without risk. Cool fire exposed containers with water from the side. As in any fire, wear NIOSH/MSHA approved, pressure demand self-contained breathing apparatus and full protective gear.

**VI. Accidental Release Measures**

Action To Take For Spills/ Leaks: Avoid contact with skin or eyes. Ventilate area, eliminate all sources of ignition. Wear appropriate protective gear, contain leak or spill, salvage, clean up residue with absorbent material.  
Waste Disposal Method: Handle disposal of waste material in manner which complies with local, state, provincial and federal regulation. Landfill if solidified, or incineration at agency approved waste-disposal facilities.

**VII. Handling And Storage**

Average Shelf Life: Refer to Product Data Sheet  
 Special Instructions: Store away from heat, open flames or sparks. Use proper grounding for bulk quantities.

**VIII. Exposure Controls / Personal Protection**

Ventilation: Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build up of heavy vapors.

**Personal Protection Equipment:** Do NOT wear contact lenses when working with this material. Use chemical goggles/safety glasses with side shields and impervious gloves. Wear clothing with long sleeves and pants. In operations where mists can be generated or the exposure limits for crystalline silica can be exceeded, wear a NIOSH/MSHA approved dust/fume respirator selected by a technically qualified person for the specific work conditions. Wear respirator protection whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH approved respirators for listed hazard.

Confined spaces, room, or tanks are areas where concern for TLV's is especially important. Reference OSHA regulation CFR 29 1910.134 for recommended respiratory protection.

## IX. Physical And Chemical Properties

Boiling Point (°C):	76.5	Water/Oil Distribution	
Percent Volatile:	97%	Coefficient:	N/A
Freezing Point (°C):	-84	Solubility in Water:	Slight
Vapor Pressure @ 20 °C:	N/A	Specific Gravity @ 20 °C:	0.9
Vapor Density:	3.4	pH:	N/A
Odor Threshold:	N/A	Evaporation Rate:	N/A
Appearance:	Clear liquid	Odor:	Fruity
N/A = Not Available	N/D=NOT Determined	Ca. = Approximate	

## X. Stability And Reactivity

HMIS Hazard Rating No. 1

<u>Stability:</u>	Stable
<u>Incompatibility:</u>	Strong bases and oxidizing agents.
<u>Hazardous Decomposition Products:</u>	Oxides of Carbon; aldehydes; Decomposition and Combustion products may be toxic.
<u>Conditions To Avoid:</u>	Strong bases in bulk.

## XI. Toxicity Information

HMIS Hazard Rating No. 1

PRIMARY ROUTE OF ENTRY: Inhalation, dermal.

Effects Of Overexposure

<u>Inhalation:</u>	Vapors/mist can be irritating to nose and mucous membranes. High exposures may result in dizziness, headaches, anesthesia, drowsiness, unconsciousness and other central nervous system effects.
<u>Eyes:</u>	Product may cause severe irritation, redness, tearing and blurred vision.
<u>Skin Contact:</u>	Frequent or prolonged contact may irritate and cause dermatitis, or aggravate an existing condition.
<u>Ingestion:</u>	Not expected to be a relevant route of exposure, although it may cause permanent damage to the mouth, throat and stomach.

**XII. Ecological Information**

Marine Pollutant: NL  
 (NL = Not Listed; P = Moderate; PP = Severe; ND - Not Determined)

**XIII. Disposal Considerations**

Handle disposal of waste material in manner which complies with all applicable local, state, provincial and federal regulations.

**XIV. Transport Information**

DOT SHIPPING INFORMATION

Shipping Name	Flammable Liquid N.O.S. (Ethyl Acetate)		
Hazard Class	3		
Identification Number	UN 1993	Packaging Group	II

**XV. Regulatory Information**

OSHA Hazard Communication Standard (29 CFR 1910.1200)	N/A
CERCLA/ Super fund (40 CFR 117, 302)	N/A
SARA Extremely Hazardous Substances (40 CFR 355)	N/A
SARA Hazard Categories (40 CFR 370)	Physical: Fire
SARA Toxic Chemicals (40 CFR 372)	None
Inventory Status	The chemicals in this product are listed on the US TSCA Chemical Substance Inventory and the Canadian Domestic Substances List.

**XVI. Other Information**

THE INFORMATION HEREIN HAS BEEN COMPLIED FROM SOURCES BELIEVED TO BE RELIABLE AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, BALCO, INC. CAN NOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE ANY WARRANTIES, NOR ASSUMES ANY LIABILITY, FOR ITS USE.