

Material Safety Data Sheet

Emergency Phone: (316) 945-9328 24-Hour CHEMTREC (800) 424-9300 CHEMTREC, D.C. Area 800-483-7616

I. Chemical Product And Company Data

PRODUCT: PRIMER 2 PART B
CHEMICAL FAMILY: Polyol and petroleum hydrocarbons
REVISION DATE: SEPTEMBER 2005
MANUFACTURER: Balco, Inc.
 2626 S. Sheridan, Wichita, KS 67217

Health	1
Flammability	2
Reactivity	1
Personal Protection	H

II. Composition / Information On Ingredients

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). Where a proprietary ingredient is shown, the identity may be made available as provided in this standard. All components of this product are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

HAZARDOUS INGREDIENTS	CAS NO	EXPOSURE LIMITS			CONTENT
		TLV	STEL	PEL	
Petroleum Hydrocarbons	64742-95-6	100ppm	N/A	N/A	25.2%
Proprietary Ingredients					Balance

California Proposition 65 ingredients

None

Section 313 Supplier Notification

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 (40 CFR 372)

1,2,4-trimethylbenzene	95-63-6	25ppm	N/A	25ppm	12.8%
Xylene	1330-20-7	100ppm	150ppm	100ppm	1.2%
Cumene	98-82-8	50ppm	N/A	50ppm	0.6%
Ethyl Benzene	100-41-4	100ppm	125ppm	100ppm	0.2%

III. Hazards Identification

HMIS Hazard Rating No. 1

PRIMARY ROUTE OF ENTRY: Eye and skin contact, breathing and ingestion.

Symptoms of Exposure

Skin Contact: Contact may cause moderate skin irritation. In some individuals exposure may result in allergic type symptoms causing rash, itching, and hives.

Eyes: Contact can cause severe irritation, redness, tearing and blurred vision.

Inhalation: Vapors can be irritating to nose and mucous membranes. Exposures may result in tightness or burning in chest, coughing, headache and fatigue. Respiratory sensitivity may result in asthma-like symptoms and on subsequent exposure even below the TLV.

Ingestion: Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly leading to death.

IV. First Aid Measures

Inhalation Remove victim from exposure. If difficulty with breathing, administer oxygen and seek medical assistance

Eyes Flush eyes with cold water for a minimum of 15 minutes, lifting lower and upper eye lids throughout. Seek immediate medical attention.

Skin Immediately remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.

Ingestion Do not induce vomiting, get immediate medical attention, if vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious person.

V. Fire Fighting Methods

HMIS Hazard Rating No. 2

Flash Point: 43 °C (110 °F) Method: Tag C.C.

General Hazard: Decomposition and combustion products may be toxic.

Auto-Ignition Temp.: 471 °C (AH)

Limits of Flammability LEL: 1.9% (AH) UEL: 12.6% (AH)

Extinguishing Media: Carbon dioxide, foam, dry chemical and water fog.

Special Fire & Unusual Hazards: Move containers from area if it can be done without risk. Cool fire exposed containers with water from the side. As in any fire, wear NIOSH/MSHA approved, pressure demand self-contained breathing apparatus and full protective gear.

VI. Accidental Release Measures

Action To Take For Spills/ Leaks: Avoid contact with skin or eyes. Ventilate area, eliminate all sources of ignition. Wear appropriate protective gear, contain leak or spill, salvage, clean up residue with absorbent material. Pump into grounded containers, and follow waste disposal method below.

Waste Disposal Method: Handle disposal of waste material in manner which complies with local, state, provincial and federal regulation. Landfill if solidified, or incineration at agency approved waste-disposal facilities.

VII. Handling And Storage

Average Shelf Life: Refer to Product Data Sheet

Special Instructions: Store in a cool, dry place. Keep away from heat, open flames or sources of sparks. Keep container closed at all times when not in use.

VIII. Exposure Controls / Personal Protection

Ventilation: Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build up of heavy vapors.

Personal Protection Equipment: Do NOT wear contact lenses when working with this material. Use chemical goggles/safety glasses with side shields and impervious gloves. Wear clothing with long sleeves and pants. In operations where mists can be generated or the exposure limits can be exceeded, wear a NIOSH/MSHA approved dust/fume respirator selected by a technically qualified person for the specific work conditions. Wear respirator protection whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH approved respirators for listed hazard. Confined spaces, room, or tanks are areas where concern for TLV's is especially important. Reference OSHA regulation CFR 29 1910.134 for recommended respiratory protection.

IX. Physical And Chemical Properties

Boiling Point (°C):	N/D	Water/Oil Distribution Coefficient:	N/A
Percent Volatile:	Ca 40% 370g/l or 3.07 lbs/gal	Solubility in Water:	Negligible
Freezing Point (°C):	N/A	Specific Gravity @ 20 °C:	0.92
Vapor Pressure @ 20 °C:	9.5	pH:	N/A
Vapor Density:	>air	Evaporation Rate:	N/A
Odor Threshold:	N/A	Odor:	Aromatic
Appearance:	Amber liquid		
N/A = Not Available	N/D=NOT Determined	Ca. = Approximate	

X. Stability And Reactivity

HMIS Hazard Rating No. 1

<u>Stability:</u>	Stable, avoid contact with moisture.
<u>Incompatibility:</u>	Strong oxidizing agents and reducing agents, strong acids, bases, amines and peroxides .
<u>Hazardous Decomposition Products:</u>	Oxides of Carbon; and nitrogen; Decomposition and Combustion products may be toxic.
<u>Conditions To Avoid:</u>	Strong acids, bases, amines and peroxides in bulk.

XI. Toxicity Information

HMIS Hazard Rating No. 1

PRIMARY ROUTE OF ENTRY: Inhalation, dermal, eyes and ingestion.

Effects Of Overexposure

<u>Inhalation:</u>	Vapors can be irritating to nose and mucous membranes.
<u>Eyes:</u>	Contact can cause severe irritation.
<u>Skin Contact:</u>	In some individuals it may cause sensitization.
<u>Ingestion:</u>	Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly leading to death.
<u>Chronic:</u>	This product does not contain chemicals considered to be carcinogenic by NTP, IARC, ACGIH, OSHA

XII. Ecological Information

Marine Pollutant: NL
 (NL = Not Listed; P = Moderate; PP = Severe; ND - Not Determined)

XIII. Disposal Considerations

Handle disposal of waste material in manner which complies with all applicable local, state, provincial and federal regulations.

XIV. Transport Information

DOT SHIPPING INFORMATION

DOT Proper Shipping Name This product is not regulated by DOT in containers of 119 gallon capacity or less.

INTERNATIONAL

DOT Proper Shipping Name	Flammable liquid, N.O.S. (petroleum distillate).		
DOT Hazard Class	3	PG III	
DOT I.D Number	UN 1993	Label(s)	Flammable

XV. Regulatory Information

OSHA Hazard Communication Standard (29 CFR 1910.1200)	Hazardous
CERCLA/ Super fund (40 CFR 117, 302)	N/A
SARA Extremely Hazardous Substances (40 CFR 355)	N/A
SARA Hazard Categories (40 CFR 370)	Health: Immediate Physical: Delayed
SARA Toxic Chemicals (40 CFR 372) Inventory Status	See section 313 advisory in section II. The chemicals in this product are listed on the US TSCA Chemical Substance Inventory and the Canadian Domestic Substances List.

XVI. Other Information

THE INFORMATION HEREIN HAS BEEN COMPLIED FROM SOURCES BELIEVED TO BE RELIABLE AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, BALCO, INC. CAN NOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE ANY WARRANTIES, NOR ASSUMES ANY LIABILITY, FOR ITS USE.